

APC-15WR2

Target Bedside Infotainment Terminal
with Handset for Instant Communication



Features

- Handset-ready for seamless nurse call system integration
- Corner two-color light bar for alarm notification
- Rockchip RK3568 Quad-core Cortex-A55 2.0GHz
- NFC for nurse identification and quick data transmission
- 2 MP camera & front speakers for tele-consultation
- 1-Gigabit Ethernet with powered LAN (802.3at)
- 31.5mm thickness designed for space-saving installation
- Android / Debian OS support



Handset
Ready



LED Indicator
For Alarms



Quick ID
Identification



Slim Design



User Friendly
Design

Specifications

System Information

Processor	Rockchip RK3568 Arm Quad Cortex-A55, up to 2.0GHz
System Memory	4GB LPDDR4
Graphic Chipset	Mali-G52 support OpenGL ES 1.1/2.0/3.2, Vulkan 1.0/1.1, OpenCL 2.0
OS Support	Android 11 / Debian 11

Expansion Slot

M.2	1 x M.2 Key B 3042 (SATA3 / USB 2.0, support SSD / LTE Module)
-----	--

Storage

Storage	64GB eMMC
Other Storage	1 x Micro SD

Display

Size	15.6"
Resolution	1920 x 1080
Luminance	400 cd/m ²
Contrast Ratio	800
Viewing Angle	170° / 170°

Touchscreen

Touch Type	Projective capacitive multi-touch up to 10 points
------------	---

I/O Ports

USB Ports	2 x USB 3.0
LAN Port	1 x RJ-45
COM Port	1 x RS-232/485 (RJ-45 Type)
Audio Port	1 x Line-out

Audio

Speaker Output	2 x 4Ω 2.0W/2.2W (MAX)
----------------	------------------------

Indicator

LED Indicator	2 x Dual color light bar
---------------	--------------------------

Ethernet

LAN Chipset	Realtek RTL8211F-CG
Ethernet Interface	10/100/1000 Base-Tx GbE compatible

Wireless Communication

Bluetooth	Optional BT 5.0
WLAN	Optional Wi-Fi 802.11ac/a/b/g/n

Data Collection

NFC	Support NFCIP-1, NFCIP-2, ISO/IEC 14443, ISO/IEC 15693, MIFARE and FeliCa
Camera	Front 2.0 MP camera

Power Requirement

DC Input	12~24VDC in/ Powered LAN
DC Input Connector	Lockable DC Jack
Adapter	Optional Input: 100 ~ 240 Vac/ 50 ~ 60Hz Output: 60W (12V/5A) adapter

Certification

Safety	CE/FCC Class B
--------	----------------


Mechanical & Environmental

Dimension (mm)	385 x 266 x 34
Weight (kg)	1.5
Construction	Plastic PC+ABS
Mounting	VESA 75 x 75 mm
Color	White
Operating Temp.	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Storage Temp.	-10°C ~ 60°C (14°F ~ 140°F)
System Fan	Fanless
IP Rating	Front panel IP65

APC-15WR2

Target Bedside Infotainment Terminal
with Handset for Instant Communication

Mechanical Drawing



Ordering Information

P/N	Description	Processor	Memory	Storage	I/O Ports (COM/USB/LAN)	Power Input	OS Support
APC-15WR2-CW49-1R	15.6" panel PC, 1920x1080, 400nits, NFC/BT/WiFi, w/o power adapter & power cord	Rockchip RK3568	4GB LPDDR4	64GB eMMC	1 COM/ 2 USB/ 1 LAN	DC 12-24V/ Powered Lan	Android 11/ Debain 11
APC-15WR2-CW49-2R	15.6" panel PC, 1920x1080, 400nits, NFC/BT/WiFi, w/ power adapter, w/o power cord	Rockchip RK3568	4GB LPDDR4	64GB eMMC	1 COM/ 2 USB/ 1 LAN	DC 12-24V/ Powered Lan	Android 11/ Debain 11
APC-15WR2-CW49H-1R	15.6" panel PC, 1920x1080, 400nits, NFC/BT/WiFi, w/ handset, w/o power adapter & power cord	Rockchip RK3568	4GB LPDDR4	64GB eMMC	1 COM/ 2 USB/ 1 LAN	DC 12-24V/ Powered Lan	Android 11/ Debain 11
APC-15WR2-CW49H-2R	15.6" panel PC, 1920x1080, 400nits, NFC/BT/WiFi, w/ handset & power adapter, w/o power cord	Rockchip RK3568	4GB LPDDR4	64GB eMMC	1 COM/ 2 USB/ 1 LAN	DC 12-24V/ Powered Lan	Android 11/ Debain 11

Packing List

Item	Quantity
APC-15WR2 Panel PC	1

Optional Items

Item	P/N
AC/DC Adapter 12V/5A 60W Screw Type	E1702031833R
Power Cord	E1702031835R

I/O Overview

